

Qty. Description

1 UNILIFT CC7 - A1



Note! Product picture may differ from actual product

Product No.: [96280968](#)

Grundfos Unilift CC pumps are single-stage submersible pumps with a low suction ability down to 3 mm water level.

The pumps are designed for pumping rainwater and grey wastewater, e.g. from

- washing machines, baths, sinks, etc. from low-lying parts of buildings up to sewer level
- cellars or buildings prone to flooding
- draining wells
- wells for surface water with inlets from roof gutters, pits, tunnels, etc.
- swimming pools, ponds or fountains.

The pumps are suitable for both stationary and portable use.

They are for automatic operation.

The pumps allow free passage of particles up to $\varnothing 10$ mm.

The motor incorporates automatic overload protection cutting out the motor in case of overload.

When cooled to normal temperature, the motor restarts automatically.

Technical:

Maximum particle size: 10 mm

Materials:

Pump housing: PP 15 GF

Impeller: PPOm 20 GF

Installation:

Pump outlet: R 1 1/4

Maximum installation depth: 10 m

Liquid:

Pumped liquid: Any Newtonian liquid

Liquid temperature range: 0 .. 40 °C

Density: 998.2 kg/m³

Electrical data:

Mains frequency: 50 Hz

Rated voltage: 1 x 220-240 V

Qty.	Description
	<p>Rated current: 1.8 A Capacitor size - run: 8 μF/450 V Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 10 m Type of cable plug: SCHUKO</p> <p>Others: Net weight: 5.27 kg Gross weight: 6.03 kg Shipping volume: 0.017 m³ Danish VVS No.: 391280371 Swedish RSK No.: 5885925 Norwegian NRF no.: 9045639</p>

Description	Value
General information:	
Product name:	UNILIFT CC7 - A1
Product No:	96280968
EAN number:	5700830761380
	5700830761380
Technical:	
Max flow:	10 m ³ /h
Head max:	7 m
Maximum particle size:	10 mm
Materials:	
Pump housing:	PP 15 GF
Impeller:	PPOm 20 GF
Installation:	
Pump outlet:	R 1 1/4
Maximum installation depth:	10 m
Liquid:	
Pumped liquid:	Any Newtonian liquid
Liquid temperature range:	0 .. 40 °C
Density:	998.2 kg/m ³
Electrical data:	
Mains frequency:	50 Hz
Rated voltage:	1 x 220-240 V
Rated current:	1.8 A
Capacitor size - run:	8 µF/450 V
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	YES
Length of cable:	10 m
Type of cable plug:	SCHUKO
Controls:	
Level switch:	float switch
Others:	
Net weight:	5.27 kg
Gross weight:	6.03 kg
Shipping volume:	0.017 m ³
Danish VVS No.:	391280371
Swedish RSK No.:	5885925
Norwegian NRF no.:	9045639

