

**Qty. Description**

1 UNILIFT CC7 - A1



Note! Product picture may differ from actual product

Product No.: [98624463](#)

Grundfos Unilift CC pumps are single-stage submersible pumps with a low suction ability down to 3 mm water level.

The pumps are designed for pumping rainwater and grey wastewater, e.g. from

- washing machines, baths, sinks, etc. from low-lying parts of buildings up to sewer level
- cellars or buildings prone to flooding
- draining wells
- wells for surface water with inlets from roof gutters, pits, tunnels, etc.
- swimming pools, ponds or fountains.

The pumps are suitable for both stationary and portable use.

They are for automatic operation.

The pumps allow free passage of particles up to  $\varnothing 10$  mm.

The motor incorporates automatic overload protection cutting out the motor in case of overload.

When cooled to normal temperature, the motor restarts automatically.

**Technical:**

Maximum particle size: 10 mm

**Materials:**

Pump housing: PP 15 GF

Impeller: PPOm 20 GF

**Installation:**

Pump outlet: R 1 1/4

Maximum installation depth: 10 m

**Liquid:**

Pumped liquid: Any Newtonian liquid

Liquid temperature range: 0 .. 40 °C

Density: 998.2 kg/m<sup>3</sup>

**Electrical data:**

Mains frequency: 50 Hz

Rated voltage: 1 x 220-240 V

Rated current: 1.8 A

Capacitor size - run: 8  $\mu$ F/450 V

Enclosure class (IEC 34-5): IP68



Company name:

Created by:

Phone:

Date:

04/04/2020

Qty.	Description
	Insulation class (IEC 85): F Length of cable: 10 m Type of cable plug: SCHUKO
	<b>Others:</b> Net weight: 5.42 kg Gross weight: 6.18 kg Shipping volume: 0.017 m <sup>3</sup> Danish VVS No.: 391280372 Swedish RSK No.: 5886000 Finnish LVI No.: 4822528

Description	Value
<b>General information:</b>	
Product name:	UNILIFT CC7 - A1
Product No:	98624463
EAN number:	5711498431317
	5711498431317
<b>Technical:</b>	
Max flow:	10 m <sup>3</sup> /h
Head max:	7 m
Maximum particle size:	10 mm
<b>Materials:</b>	
Pump housing:	PP 15 GF
Impeller:	PPOm 20 GF
<b>Installation:</b>	
Pump outlet:	R 1 1/4
Maximum installation depth:	10 m
<b>Liquid:</b>	
Pumped liquid:	Any Newtonian liquid
Liquid temperature range:	0 .. 40 °C
Density:	998.2 kg/m <sup>3</sup>
<b>Electrical data:</b>	
Mains frequency:	50 Hz
Rated voltage:	1 x 220-240 V
Rated current:	1.8 A
Capacitor size - run:	8 µF/450 V
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	YES
Length of cable:	10 m
Type of cable plug:	SCHUKO
<b>Controls:</b>	
Level switch:	float switch
<b>Others:</b>	
Net weight:	5.42 kg
Gross weight:	6.18 kg
Shipping volume:	0.017 m <sup>3</sup>
Danish VVS No.:	391280372
Swedish RSK No.:	5886000
Finnish LVI No.:	4822528

