

Qty. Description

1 Unilift KP 250 A 1



Note! Product picture may differ from actual product

Product No.: [012H1600](#)

Submersible drainage pump

Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase canned motor in insulation class F with thermal overload protection.

The pump is fitted with suction strainer and a carrying handle and is supplied with a 5 m mains cable and float switch for automatic start and stop.

The impeller is a semi-open impeller for 10 mm free passage suitable for pumping groundwater, surface water, rain water and similar liquids.

The pump has a double shaft seal consisting of two lip seals with grease in-between.

The pump has an outer casing ensuring continuous cooling of the motor by the pumped liquid. The rotor shaft operates in two maintenance-free carbon bearings cooled by the pumped liquid.

The motor is filled with a non-toxic motor liquid.

Liquid:

Pumped liquid: Any Newtonian liquid

Liquid temperature range: 0 .. 50 °C

Density: 998.2 kg/m³

Technical:

Maximum particle size: 10 mm

Qty.	Description
	<p>Materials:</p> <p>Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Impeller: Stainless steel DIN W.-Nr. 1.4031 AISI 304</p> <p>Installation:</p> <p>Pump outlet: Rp 1 1/4 Maximum installation depth: 2 m</p> <p>Electrical data:</p> <p>Power input - P1: 480 W Mains frequency: 50 Hz Rated voltage: 1 x 220-230 V Rated current: 2.3 A Capacitor size - run: 8 µF/400 V Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 5 m Type of cable plug: SCHUKO</p> <p>Others:</p> <p>Net weight: 6.3 kg Gross weight: 6.8 kg Shipping volume: 0.013 m³ Danish VVS No.: 391215025 Country of origin: HU Custom tariff no.: 84137021</p>

Description	Value
General information:	
Product name:	Unilift KP 250 A 1
Product No:	012H1600
EAN number:	5700391116575
	5700391116575
Price:	432,00 EUR
Technical:	
Max flow:	3.11 l/s
Head max:	7.5 m
Maximum particle size:	10 mm
Model:	A
Materials:	
Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Stainless steel DIN W.-Nr. 1.4031 AISI 304
Installation:	
Pump outlet:	Rp 1 1/4
Maximum installation depth:	2 m
Liquid:	
Pumped liquid:	Any Newtonian liquid
Liquid temperature range:	0 .. 50 °C
Density:	998.2 kg/m ³
Electrical data:	
Power input - P1:	480 W
Mains frequency:	50 Hz
Rated voltage:	1 x 220-230 V
Rated current:	2.3 A
Capacitor size - run:	8 µF/400 V
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	CONTACT
Thermal protec:	internal
Length of cable:	5 m
Type of cable plug:	SCHUKO
Controls:	
Level switch:	float switch
Others:	
Net weight:	6.3 kg
Gross weight:	6.8 kg
Shipping volume:	0.013 m ³
Danish VVS No.:	391215025
Country of origin:	HU
Custom tariff no.:	84137021

