

Qty. Description

1 Unilift KP 350 A 1



Note! Product picture may differ from actual product

Product No.: [013N1600](#)

Submersible drainage pump

Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase canned motor in insulation class F with thermal overload protection.

The pump is fitted with suction strainer and a carrying handle and is supplied with a 5 m mains cable and float switch for automatic start and stop.

The impeller is a semi-open impeller for 10 mm free passage suitable for pumping groundwater, surface water, rain water and similar liquids.

The pump has a double shaft seal consisting of two lip seals with grease in-between.

The pump has an outer casing ensuring continuous cooling of the motor by the pumped liquid.

The rotor shaft operates in two maintenance-free carbon bearings cooled by the pumped liquid.

The motor is filled with a non-toxic motor liquid.

Liquid:

Pumped liquid: Any Newtonian liquid

Liquid temperature range: 0 .. 50 °C

Density: 998.2 kg/m³

Technical:

Maximum particle size: 10 mm

Qty.	Description																																						
	<p>Materials:</p> <table><tr><td>Pump housing:</td><td>Stainless steel DIN W.-Nr. 1.4301 AISI 304</td></tr><tr><td>Impeller:</td><td>Stainless steel DIN W.-Nr. 1.4031 AISI 304</td></tr></table> <p>Installation:</p> <table><tr><td>Pump outlet:</td><td>Rp 1 1/4</td></tr><tr><td>Maximum installation depth:</td><td>2 m</td></tr></table> <p>Electrical data:</p> <table><tr><td>Power input - P1:</td><td>700 W</td></tr><tr><td>Mains frequency:</td><td>50 Hz</td></tr><tr><td>Rated voltage:</td><td>1 x 220-240 V</td></tr><tr><td>Rated current:</td><td>3.2 A</td></tr><tr><td>Capacitor size - run:</td><td>10 µF/400 V</td></tr><tr><td>Enclosure class (IEC 34-5):</td><td>IP68</td></tr><tr><td>Insulation class (IEC 85):</td><td>F</td></tr><tr><td>Length of cable:</td><td>5 m</td></tr><tr><td>Type of cable plug:</td><td>SCHUKO</td></tr></table> <p>Others:</p> <table><tr><td>Net weight:</td><td>7 kg</td></tr><tr><td>Gross weight:</td><td>7.5 kg</td></tr><tr><td>Shipping volume:</td><td>0.013 m³</td></tr><tr><td>Danish VVS No.:</td><td>391215035</td></tr><tr><td>Country of origin:</td><td>HU</td></tr><tr><td>Custom tariff no.:</td><td>84137021</td></tr></table>	Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304	Impeller:	Stainless steel DIN W.-Nr. 1.4031 AISI 304	Pump outlet:	Rp 1 1/4	Maximum installation depth:	2 m	Power input - P1:	700 W	Mains frequency:	50 Hz	Rated voltage:	1 x 220-240 V	Rated current:	3.2 A	Capacitor size - run:	10 µF/400 V	Enclosure class (IEC 34-5):	IP68	Insulation class (IEC 85):	F	Length of cable:	5 m	Type of cable plug:	SCHUKO	Net weight:	7 kg	Gross weight:	7.5 kg	Shipping volume:	0.013 m ³	Danish VVS No.:	391215035	Country of origin:	HU	Custom tariff no.:	84137021
Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304																																						
Impeller:	Stainless steel DIN W.-Nr. 1.4031 AISI 304																																						
Pump outlet:	Rp 1 1/4																																						
Maximum installation depth:	2 m																																						
Power input - P1:	700 W																																						
Mains frequency:	50 Hz																																						
Rated voltage:	1 x 220-240 V																																						
Rated current:	3.2 A																																						
Capacitor size - run:	10 µF/400 V																																						
Enclosure class (IEC 34-5):	IP68																																						
Insulation class (IEC 85):	F																																						
Length of cable:	5 m																																						
Type of cable plug:	SCHUKO																																						
Net weight:	7 kg																																						
Gross weight:	7.5 kg																																						
Shipping volume:	0.013 m ³																																						
Danish VVS No.:	391215035																																						
Country of origin:	HU																																						
Custom tariff no.:	84137021																																						

Description	Value
General information:	
Product name:	Unilift KP 350 A 1
Product No:	013N1600
EAN number:	5700393433137
	5700393433137
Price:	550,00 EUR
Technical:	
Max flow:	3.89 l/s
Head max:	9 m
Maximum particle size:	10 mm
Model:	A
Materials:	
Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Stainless steel DIN W.-Nr. 1.4031 AISI 304
Installation:	
Pump outlet:	Rp 1 1/4
Maximum installation depth:	2 m
Liquid:	
Pumped liquid:	Any Newtonian liquid
Liquid temperature range:	0 .. 50 °C
Density:	998.2 kg/m ³
Electrical data:	
Power input - P1:	700 W
Mains frequency:	50 Hz
Rated voltage:	1 x 220-240 V
Rated current:	3.2 A
Capacitor size - run:	10 µF/400 V
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	CONTACT
Thermal protec:	internal
Length of cable:	5 m
Type of cable plug:	SCHUKO
Controls:	
Level switch:	float switch
Others:	
Net weight:	7 kg
Gross weight:	7.5 kg
Shipping volume:	0.013 m ³
Danish VVS No.:	391215035
Country of origin:	HU
Custom tariff no.:	84137021

