

Qty. Description

1 Unilift AP50B.50.08.1.V



Note! Product picture may differ from actual product

Product No.: [96004587](#)

Submersible effluent pump

Vertical single-stage stainless steel submersible pump with integrated submersible 1-phase motor.

The pump is fitted with ring stand and carrying handle and is supplied with a 10 m mains cable.

The impeller is a VORTEX impeller for 50 mm free passage suitable for pumping surface water, groundwater, wastewater and similar.

The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.

The motor is insulation class F with thermal overload protection and has long-life deep-groove greased-for-life ball bearings.

The pump has R 2" discharge port and is ready for installation either free-standing or on an auto-coupling system.

Liquid:

Pumped liquid: Any Newtonian liquid

Maximum liquid temperature: 40 °C

Density: 998.2 kg/m³

Technical:

Type of impeller: VORTEX

Qty.	Description
	Maximum particle size: 50 mm
	Materials:
	Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304
	Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304
	Installation:
	Pump outlet: R 2"
	Maximum installation depth: 7 m
	Auto-coupling: Y
	Electrical data:
	Type of motor: PSC
	Power input - P1: 1.2 kW
	Mains frequency: 50 Hz
	Rated voltage: 1 x 230 V
	Rated current: 5.37 A
	Cos phi - power factor: 0.97
	Rated speed: 2790 rpm
	Capacitor size - run: 16 µF/400 V
	Enclosure class (IEC 34-5): IP68
	Insulation class (IEC 85): F
	Length of cable: 10 m
	Type of cable plug: SCHUKO
	Others:
	Net weight: 11.5 kg
	Gross weight: 12.5 kg
	Danish VVS No.: 391272112
	Swedish RSK No.: 5885937
	Finnish LVI No.: 4822589

Description	Value
General information:	
Product name:	Unilift AP50B.50.08.1.V
Product No:	96004587
EAN number:	5700391489549
	5700391489549
Technical:	
Max flow:	24 m³/h
Head max:	11 m
Type of impeller:	VORTEX
Maximum particle size:	50 mm
Materials:	
Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Installation:	
Pump outlet:	R 2"
Maximum installation depth:	7 m
Inst dry/wet:	S
Installation:	horizontal or vertical
Auto-coupling:	Y
Liquid:	
Pumped liquid:	Any Newtonian liquid
Maximum liquid temperature:	40 °C
Density:	998.2 kg/m³
Electrical data:	
Type of motor:	PSC
Power input - P1:	1.2 kW
P2:	0.74 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Rated current:	5.37 A
Cos phi - power factor:	0.97
Rated speed:	2790 rpm
Capacitor size - run:	16 µF/400 V
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	CONTACT
Thermal protec:	internal
Length of cable:	10 m
Type of cable plug:	SCHUKO
Others:	
Net weight:	11.5 kg
Gross weight:	12.5 kg
Danish VVS No.:	391272112
Swedish RSK No.:	5885937
Finnish LVI No.:	4822589

