

Wall mounted unit

FTXF-C + RXF-C



Energy saving during standby mode



Online controller

Wall mounted unit for low energy consumption and pleasant comfort

- › Seasonal efficiency values up to A++ in cooling
- › Online controller (optional)
- › Quiet in operation
- › Bluevolution range: lower environmental impact

FTXF-C + RXF-C



FTXF-C



RXF-C

Indoor unit			FTXF	20C	25C	35C	42C	
Dimensions	Unit	HeightxWidthxDepth	mm	286 x770 x225				
Weight	Unit		kg	8.00		8.50	9.00	
Air filter	Type			Removable / washable				
Fan	Air flow rate	Cooling	Silent operation/Low/ Medium/High	m ³ /min	3.6 /4.6 /6 /8.3	3.6 /4.6 /6 /8.5	4.4 /6.4 /8 /11.8	4.9 /6.9 /9 /12.6
		Heating	Silent operation/Low/ Medium/High	m ³ /min	4.6 / 5.8 / 7.8 / 9.7	4.6 / 6.0 / 7.9 / 9.7	5.3 / 6.5 / 8.6 / 11.9	5.2 / 6.7 / 8.8 / 12.8
Sound power level	Cooling		dBA	53.0		54.0		59.0
	Heating		dBA	55.0		56.0		59.0
Sound pressure level	Cooling	Silent operation/Low/High	dBA	20.0 /25.0 /39.0	20.0 /26.0 /40.0	20.0 /27.0 /43.0	22.0 /30.0 /45.0	
	Heating	Silent operation/Low/High	dBA	21.0 /28.0 /39.0	21.0 /28.0 /40.0	21.0 /29.0 /40.0	22.0 /28.0 /44.0	
Control systems	Infrared remote control			ARC470A1				
	Wired remote control			BRC073A1				
Outdoor unit			RXF	20C	25C	35C	42C	
Dimensions	Unit	HeightxWidthxDepth	mm	550 x658 x275				
Weight	Unit		kg	25.5		26.0	28.0	
Sound power level	Cooling		dBA	60.0		61.0		
	Heating		dBA	60.0		62.0		
Sound pressure level	Cooling	High	dBA	46.0		48.0		
	Heating	High	dBA	47.0		48.0		
Operation range	Cooling	Ambient	Min.-Max.	°CDB -10 ~46				
Refrigerant	Type			R-32				
	GWP			675.0				
	Charge		kg/TCO2Eq	0.450 /0.300		0.550 /0.370	0.750 /0.510	
Piping connections	Liquid	OD	mm	6.35				
	Gas	OD	mm	9.50				
	Piping length	OU - IU	Max.	m 20				
	Additional refrigerant charge		kg/m	0.02 (for piping length exceeding 10m)				
	Level difference	IU - OU	Max.	m 12.0				
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50 /220-240				
Current - 50Hz	Maximum fuse amps (MFA)		A	16				
Efficiency data			FTXF + RXF	20C + 20C	25C + 25C	35C + 35C	42C + 42C	
Cooling capacity	Min./Nom./Max.		kW	1.3 /2.00 /2.4	1.3 /2.50 /2.8	1.3 /3.30 /3.8	1.4 /4.20 /4.3	
Heating capacity	Min./Nom./Max.		kW	1.30 /2.40 /3.30	1.30 /2.80 /3.70	1.30 /3.50 /4.40	1.40 /4.60 /5.00	
Power input	Cooling	Min./Nom./Max.	kW	0.31 /0.592 /0.72	0.31 /0.772 /1.05	0.31 /1.00 /1.40	0.31 /1.27 /1.50	
	Heating	Min./Nom./Max.	kW	0.25 /0.640 /0.95	0.25 /0.750 /1.11	0.25 /0.940 /1.50	0.25 /1.24 /1.40	
Space cooling	Energy efficiency class			A++				
	Capacity	Pdesign	kW	2.00	2.50	3.50	4.20	
	SEER			6.22				
	Annual energy consumption		kWh/a	113	141	197	226	
Space heating (Average climate)	Energy efficiency class			A+				
	Capacity	Pdesign	kW	2.20	2.40	2.60	3.30	
	SCOP/A			4.11				
	Annual energy consumption		kWh/a	749	817	885	1,075	
Nominal efficiency	EER			3.38		3.30		
	COP			3.75		3.71		
Energy labeling Directive Cooling/Heating				A/A				

Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. Data for high efficiency series, Eurovent certified | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. Data for standard efficiency series | See separate drawing for electrical data

Daikin Europe N.V. Naamloze Venootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN21-050A

02/2021

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

