



Wall mounted unit

FTXC-C / RXC-C

BLUEEVOLUTION sensira



Energy saving during standby mode



Online controller via app

Wall mounted unit, offering good value for money

- › Flat, stylish front panel blends easily with any interior décor and is easier to clean
- › Online controller (optional)

- › Seasonal efficiency values up to A++ in cooling
- › Bluevolution range: lower environmental impact

FTXC-C / RXC-C



FTXC-C




RXC20-35C

Efficiency data		FTXC + RXC	20C + 20C	25C + 25C	35C + 35C	50C + 50C	60C + 60C	71C + 71C
Cooling capacity	Min./Max.	kW	1.3 /3.0		1.3 /4.0	1.4 /6.2	1.8 /7.0	2.3 /7.3
Heating capacity	Min./Max.	kW	1.30 /4.00		1.30 /4.80	1.36 /6.60	1.48 /8.00	2.30 /9.00
Space cooling	Energy efficiency class		A++					A
	Capacity	Pdesign	kW	2.08	2.57	3.44	5.08	6.96
	SEER			6.89	6.84	6.87	6.45	6.40
	η _{s,c}		%	-				
Space heating (Average climate)	Annual energy consumption		kWh/a	106	132	175	276	340
	Energy efficiency class			A+				
	Capacity	Pdesign	kW	1.87	2.23	2.24	3.90	4.10
	SCOP/A			4.40	4.45	4.28	4.42	4.24
	η _{s,h}		%	-				
Annual energy consumption		kWh/a	594	700	732	1,236	1,354	

Indoor unit		FTXC	20C	25C	35C	50C	60C	71C	
Dimensions	Unit	HeightxWidthxDepth	mm			288 x770 x234		297 x990 x273	
Weight	Unit		kg		9.00		9.50		
Air filter	Type		Removable / washable					13.0	
Fan	Air flow rate	Cooling	Silent operation/Low/Medium/High	m ³ /min		5.4 /6.5 /9 /10.8		7.4 /8.2 /10 /12.2	
Sound power level	Cooling			dBA		54		55	
Sound pressure level	Cooling	Silent operation/Low/High		dBA		20 /26 /38		21 /26 /39	
Control systems	Infrared remote control		ARC486A2					-	
	Wired remote control								

Outdoor unit		RXC	20C	25C	35C	50C	60C	71C	
Dimensions	Unit	HeightxWidthxDepth	mm			550 x658 x273		615 x845 x300	
Weight	Unit		kg		24.0		26.0		
Sound power level	Cooling		dBA		58		60		
Sound pressure level	Cooling	High	dBA		45		46		
Operation range	Cooling	Ambient	Min.~Max.	°CDB		10 ~46		-10 ~46	
	Heating	Ambient	Min.~Max.	°CWB		-15 ~18			
Refrigerant	Type		R-32						
	GWP		675.0						
Piping connections	Charge		kg/CO ₂ Eq		0.550 /0.371		0.750 /0.506		
	Liquid	OD	mm		6.4		1.00 /0.675		
	Gas	OD	mm		9.52		1.10 /0.743		
	Piping length	OU - IU	Max.	m		20		30	
	Additional refrigerant charge	System	Chargeless	m		8			
Power supply	Level	IU - OU	Max.	m		15.0		20.0	
	Phase/Frequency/Voltage		Hz/V		1~/50 /220-240				
Current - 50Hz	Maximum fuse amps (MFA)		A		16				

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN21-045 12/2020



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.