

Qty. Description1 **Float switch MS1, 10m cable****Note! Product picture may differ from actual product**Product No.: [96003332](#)

Float switch MS1 is engineered especially for use in sewage works and pumping stations with liquids heavily charged with solid matter such as raw sewage etc.

Thanks to the good chemical and thermal properties our level controllers are resistant to lees, uric acid, fecal sewage water, oils, petrol, diesel oil, emulsions, alcohol, fruit acids, and even many chemicals.

For use at temperatures of up to 80 °C (176 °F).

Liquid:

Maximum liquid temperature: 80 °C

Technical:

Approvals on nameplate: CE,EAC

Signal output: SPDT switch

Materials:

Enclosure: PP

Cable surface: TPK-PVC

Electrical data:

Enclosure class (IEC 34-5): IP68

Cable included (Yes/No): Y

Length of cable: 10 m

Power plug: cable without connector

Min. rated voltage dc: 4.00 V

Max. rated voltage dc: 250.00 V

Others:

Net weight: 1.31 kg

Gross weight: 1.44 kg

Shipping volume: 0.005 m³

Danish VVS No.: 391371691

Swedish RSK No.: 6008602

Norwegian NRF no.: 9045177

Custom tariff no.: 90261089

Description	Value
General information:	
Product name:	Float switch MS1, 10m cable
Product No:	96003332
EAN number:	5708601065453
	5708601065453
Technical:	
Approvals on nameplate:	CE,EAC
Signal output:	SPDT switch
Materials:	
Enclosure:	PP
Cable surface:	TPK-PVC
Liquid:	
Maximum liquid temperature:	80 °C
Electrical data:	
Enclosure class (IEC 34-5):	IP68
Cable included (Yes/No):	Y
Length of cable:	10 m
Power plug:	cable without connector
Min. rated voltage dc:	4.00 V
Max. rated voltage dc:	250.00 V
Others:	
Brand:	GRUNDFOS
Net weight:	1.31 kg
Gross weight:	1.44 kg
Shipping volume:	0.005 m ³
Danish VVS No.:	391371691
Swedish RSK No.:	6008602
Norwegian NRF no.:	9045177
Custom tariff no.:	90261089