

Company name: Created by: Phone:

Date: 17/04/2020

Qty. | Description

1 MAGNA1 100-80 F



Note! Product picture may differ from actual product

Product No.: 99221440

The new MAGNA1 is the simple option for a job well done. It is the perfect choice when replacing older circulators and due to its compliance with the EuP 2015 regulations, substantial savings on electricity is a reality. The ideal choice for basic performance needs in applications where basic system control and monitoring is desired.

- · Monitoring via the fault relay, ensuring peace of mind
- Digital start/stop input available for remote pump control
- Continuous operation and reduced downtime with the wireless twin pump function (available on twin-head pumps)
- · High energy efficiency resulting in substantial savings on electricity
- · Easy setup and operation via the simple user interface
- No maintenance due to the canned-rotor type design.

MAGNA1 is the simple and efficient choice for most applications including

- Heating
 - Main pump
 - Mixing loops
 - Heating surfaces
- Cooling
 - Air conditioning surfaces
 - Ground source heat pump systems
 - Smaller chiller applications

Liquid:

Pumped liquid: Water
Liquid temperature range: -10 .. 110 °C
Selected liquid temperature: 60 °C
Density: 983.2 kg/m³

Technical:

TF class: 110

Approvals on nameplate: CE, VDE, EAC, CN ROHS, WEEE

Materials:

Pump housing: Cast iron

EN-GJL-250 ASTM A48-250B

Impeller: PES 30%GF

Installation:

Range of ambient temperature: 0 .. 40 °C
Maximum operating pressure: 6 bar
Flange standard: DIN
Pipe connection: DN 100
Pressure rating: PN6
Port-to-port length: 450 mm



Company name: Created by: Phone:

Date: 17/04/2020

Qty. | Description

Electrical data:

Power input - P1: 31.42 .. 1067 W
Mains frequency: 50 / 60 Hz
Rated voltage: 1 x 230 V
Maximum current consumption: 0.32 .. 4.71 A

Enclosure class (IEC 34-5): X4D Insulation class (IEC 85): F

Others:

Energy (EEI):

Net weight:

Gross weight:

Shipping volume:

Country of origin:

Custom tariff no.:

0.19

34 kg

36.7 kg

0.097 m³

DE

84137030



Company name: Created by: Phone:

Date: 17/04/2020

-	v .
Description General information:	Value
Product name:	MAGNA1 100-80 F
Product No:	99221440
EAN number:	5712608944123
EAN number.	** :-**** * : :-*
Price:	5712608944123
Technical:	2.719,00 EUR
Head max:	90 dm
TF class:	80 dm 110
Approvals on nameplate:	CE,VDE,EAC,CN ROHS,WEEE
Model:	С
Materials:	On at image
Pump housing:	Cast iron
	EN-GJL-250
	ASTM A48-250B
Impeller:	PES 30%GF
Installation:	
Range of ambient temperature:	0 40 °C
Maximum operating pressure:	6 bar
Flange standard:	DIN
Pipe connection:	DN 100
Pressure rating:	PN6
Port-to-port length:	450 mm
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-10 110 °C
Selected liquid temperature:	60 °C
Density:	983.2 kg/m³
Electrical data:	
Power input - P1:	31.42 1067 W
Mains frequency:	50 / 60 Hz
Rated voltage:	1 x 230 V
Maximum current consumption:	0.32 4.71 A
Enclosure class (IEC 34-5):	X4D
Insulation class (IEC 85):	F
Others:	
Energy (EEI):	0.19
Net weight:	34 kg
Gross weight:	36.7 kg
Shipping volume:	0.097 m³
Country of origin:	DE
Custom tariff no.:	84137030



