

1

UPS 25-40 N 180



μ !

μ

: [96913060](#)

The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid. The pump has 3-step speed selector.

The pump is characterized by:

- * Ceramic shaft and radial bearings.
- * Carbon axial bearing.
- * Stainless steel rotor can and bearing plate.
- * Corrosion-resistant impeller, PES/PP.
- * pump housing.

The motor is a 1-phase motor.

No additional motor protection is required.

μ : Water
μ : 2 .. 110 °C
μ : 60 °C
μ : 983.2 kg/m³

TF: 110
: CE, VDE, EAC, WEEE

μ : DIN W.-Nr. 1.4301
: PES/PP

μ. : 80 C: 40 °C
: 10 bar
: G 1 1/2
μ : PN 10
μ : 180 mm

: 1: 25 W
: 2: 35 W
: 45 W
: 50 Hz

Rated voltage: 1 x 230 V

μ	1:	0.12 A
μ	2:	0.16 A
μ	3:	0.2 A
-	:	1.5 μF
μ	(IEC 34-5):	IP44
μ	(IEC 85):	F
:		
:		2.9 kg
:		3.1 kg
:		0.004 m ³
Danish VVS No.:		380481041
Swedish RSK No.:		5803098
:		RS
μ	:	84137030

μ μ :
μ μ :
μ μ : 3/4/2020

μ	
μ :	UPS 25-40 N 180
μ :	96913060
μ :	5700313543083
μ :	5700313543083
μ :	458,12 EUR
μ :	3
μ μ :	40 dm
TF:	110
μ :	CE,VDE,EAC,WEEE
μ :	DIN W.-Nr. 1.4301
μ :	, PES/PP
μ μ :	80 C: 40 °C
μ :	10 bar
μ :	G 1 1/2
μ μ :	PN 10
μ μ μ :	180 mm
μ :	Water
μ μ :	2 .. 110 °C
μ :	60 °C
μ :	983.2 kg/m³
μ 1:	25 W
μ 2:	35 W
μ :	45 W
μ :	50 Hz
Rated voltage:	1 x 230 V
μ 1:	0.12 A
μ 2:	0.16 A
μ 3:	0.2 A
μ :	1.5 μF
μ (IEC 34-5):	IP44
μ (IEC 85):	F
μ :	
μ :	
μ :	9H
μ :	2.9 kg
μ :	3.1 kg
μ :	0.004 m³
Danish VVS No.:	380481041
Swedish RSK No.:	5803098
μ :	RS
μ μ :	84137030

