

1

UPS 25-60 N 180



μ !

μ

: [96913085](#)

The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid. The pump has 3-step speed selector.

The pump is characterized by:

- * Ceramic shaft and radial bearings.
- * Carbon axial bearing.
- * Stainless steel rotor can and bearing plate.
- * Corrosion-resistant impeller, PES/PP.
- * pump housing.

The motor is a 1-phase motor.

No additional motor protection is required.

μ : Water
μ : 2 .. 110 °C
μ : 60 °C
μ : 983.2 kg/m³

TF: 110
: CE, VDE, EAC, WEEE

μ :
: DIN W.-Nr. 1.4301
: , PES/PP

μ. : 80 C: 40 °C
: 10 bar
: G 1 1/2
μ : PN 10
μ : 180 mm

:
1: 50 W
2: 55 W
: 60 W
: 50 Hz
Rated voltage: 1 x 230 V

μ	1:	0.21 A
μ	2:	0.25 A
μ	3:	0.28 A
-	:	2.5 μF
μ	(IEC 34-5):	IP44
μ	(IEC 85):	F
:		
:		2.9 kg
:		3.1 kg
:		0.004 m ³
Danish VVS No.:		380481061
Swedish RSK No.:		5803097
:		4615616
Norwegian NRF no.:		9042215
:		RS
μ	:	84137030

UPS 25-60 N 180	
96913085	
5700313543465	
5700313543465	
514,09 EUR	
3	
60 dm	
TF: 110	
CE,VDE,EAC,WEEE	
DIN W.-Nr. 1.4301	
, PES/PP	
80 C:	40 °C
	10 bar
	G 1 1/2
	PN 10
	180 mm
Water	
2 .. 110 °C	
60 °C	
983.2 kg/m³	
1:	50 W
2:	55 W
	60 W
	50 Hz
Rated voltage: 1 x 230 V	
1:	0.21 A
2:	0.25 A
3:	0.28 A
	2.5 µF
(IEC 34-5):	IP44
(IEC 85):	F
9H	
2.9 kg	
3.1 kg	
0.004 m³	
Danish VVS No.: 380481061	
Swedish RSK No.: 5803097	
4615616	
Norwegian NRF no.: 9042215	
RS	
84137030	

