

1

COMFORT 15-14 BX PM



: [97916772](#)

The Grundfos Comfort PM is designed for recirculation of domestic hot water in single- and two-family houses. It has a lead-free pump housing suitable for potable water and is powered by a high-efficiency single-phase, 12-pole permanent-magnet motor.

Features and benefits:

- * Quick and simple electrical installation due to 1,5m cable incl. power plug
- * Dry-running detection
- * Easy-to-clean and lime-insensitive spheric rotor
- * Wearless operation due to liquid-lubricated bearing
- * No leakage risk due to a static seal
- * Easy maintenance and cleaning through the easy-to-separate pump head fitting almost all competitor pump housings
- * Corrosion-resistant lead-free brass pump housing
- * No additional motor protection necessary due to integrated motor electronics
- * No additional installation costs due to integrated non-return and isolating valve in included fittings

μ : Water
μ : 2 .. 95 °C
μ : 60 °C
μ : 983.2 kg/m³
TF: 95
: CE, VDE, EAC, WEEE
μ : MS 68
: , EPDM, PPO, PTFE,
: 10 bar
: G
: 1
μ μ : 140 mm
: 7 W
: 50 / 60 Hz
Rated voltage: 1 x 230 V

μ 3: 0.07 A
- : 0.6 μF
μ (IEC 34-5): IP44
μ (IEC 85): F
:
:
: 1.35 kg
: 1.51 kg
: 0.003 m³
Danish VVS No.: 380635110
Swedish RSK No.: 5803086

COMFORT 15-14 BX PM	
Model	COMFORT 15-14 BX PM
Part number	97916772
SKU	5710626363773
SKU	5710626363773
Speed	1
Impeller diameter	14 dm
TF	95
Certification	CE, VDE, EAC, WEEE
Material	MS 68, EPDM, PPO, PTFE
Pressure	10 bar
Connection	G
Impeller diameter	140 mm
Medium	Water
Temperature range	2 .. 95 °C
Operating temperature	60 °C
Density	983.2 kg/m ³
Power	7 W
Frequency	50 / 60 Hz
Rated voltage	1 x 230 V
Current	0.07 A
Capacitance	0.6 µF
Protection class (IEC 34-5)	IP44
Protection class (IEC 85)	F
Weight	1.35 kg
Volume	1.51 kg
Volume	0.003 m ³
Danish VVS No.:	380635110
Swedish RSK No.:	5803086

