

**Reflex Exvoid A 76.1, Micro bubble
separator Welding connection,110°C,10bar
Article-No.:8251110**



Reflex Exvoid,
air/microbubble separator for heating
and cooling systems respectively for
sealed system circuits.

Suitable for use with water and
water/glycol mixture to a maximum of 50%
concentration.

Removes circulating free air and gas
bubbles with high efficiency from the
system flow. Permanent evacuation by way
of integrated Exvoid-T automatic air vent
with high venting capacity. Facilitating
hydraulic balancing after filling
operations with minimum pressure drop.

Merkmale

Type: A 76.1
Housing material: Stahl, lackiert
Installation model: horizontal
Connection type: Schweißstutzen
System connection: 76,1 mm
max. operating pressure: 10 bar
max. operating temperature: 110 °C
max. flow: 20 m³/h
kvs: 121,7 m³/h
Length: 260 mm
Height: 625 mm
Diameter: 132 mm
Weight: 6,5 kg



11.03.2020 19:05

Reflex Winkelmann GmbH

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • www.reflex.de
Geschäftsführer: Norbert Hülsmann, Volker Mauel
USt.-Ident-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen