

Reflex Exvoid A 114.3, Micro bubble separator Welding connection, 110°C, 10 bar
Article-No.: 8251130

reflex

Reflex Exvoid, air/microbubble separator for heating and cooling systems respectively for sealed system circuits.

Suitable for use with water and water/glycol mixture to a maximum of 50% concentration.

Removes circulating free air and gas bubbles with high efficiency from the system flow. Permanent evacuation by way of integrated Exvoid-T automatic air vent with high venting capacity. Facilitating hydraulic balancing after filling operations with minimum pressure drop.

Merkmale

Type: A 114.3
Housing material: Stahl, lackiert
Installation model: horizontal
Connection type: Schweißstutzen
System connection: 114,3 mm
max. operating pressure: 10 bar
max. operating temperature: 110 °C
max. flow: 47 m³/h
kvs: 244,3 m³/h
Length: 370 mm
Height: 740 mm
Diameter: 206 mm
Weight: 9 kg



11.03.2020 19:05

Reflex Winkelmann GmbH

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • www.reflex.de
Geschäftsführer: Norbert Hülsmann, Volker Mauel
USt.-Ident.-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen