

**Reflex Exvoid A 273.0, Micro bubble  
separator Welding connection,110°C,10bar  
Article-No.:8251170**



Reflex Exvoid,  
air/microbubble separator for heating  
and cooling systems respectively for  
sealed system circuits.

Suitable for use with water and  
water/glycol mixture to a maximum of 50%  
concentration.

Removes circulating free air and gas  
bubbles with high efficiency from the  
system flow. Permanent evacuation by way  
of integrated Exvoid-T automatic air vent  
with high venting capacity. Facilitating  
hydraulic balancing after filling  
operations with minimum pressure drop.

---

## **Merkmale**

Type: A 273.0  
Housing material: Stahl, lackiert  
Installation model: horizontal  
Connection type: Schweißstutzen  
System connection: 273,0 mm  
max. operating pressure: 10 bar  
max. operating temperature: 110 °C  
max. flow: 288 m<sup>3</sup>/h  
kvs: 1185,7 m<sup>3</sup>/h  
Length: 750 mm  
Height: 1402 mm  
Diameter: 480 mm  
Weight: 70 kg



11.03.2020 19:05

### **Reflex Winkelmann GmbH**

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • [www.reflex.de](http://www.reflex.de)  
Geschäftsführer: Norbert Hülsmann, Volker Mauel  
USt.-Ident-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen