Reflex Exdirt D 1 M, threaded dirt separator, 110 °C, 10 bar Article-No.:9256020

Reflex Exdirt Magnet
Dirt and sludge separator for heating

and cooling water systems or closed

liquid-filled plant systems.

Suitable for the media water and water/glycol mixtures up to a mixing ratio of 50/50%.

Integrated high-energy permanent magnet for separating and fixing of ferromagnetic parts from the separation process. Magnet comprises an isostatically pressed neodymium-iron-boron rod inserted in a screw-in immersion sleeve. Particles can be permanently and deliberately removed from the fluid flow by screwing the magnet sleeve out of the separator housing and then cleaning it.



The cleaning and emptying of the dirt collection chamber is possible via a dedicated desludging ball valve without any necessity to interrupt operation.

Merkmale

Type: D 1 M

Housing material: Messing
Installation model: horizontal
Connection type: Gewinde
System connection: IG 1
Drain connection: G 3/4
max. operating pressure: 10 bar
max. operating temperature: 110 °C

max. flow: 2 m³/h kvs: 17,2 m³/h Length: 88 mm Height: 132 mm

Diametre: 65 mm Weight: 1,2 kg



11.03.2020 19:19

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • www.reflex.de Geschäftsführer: Norbert Hülsmann, Volker Mauel

USt.-Ident-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen