

Reflex Exdirt D 22 VM, dirt separator, clamping ring, 110 °C, 10 bar

Article-No.:9256500



Reflex Exdirt Magnet
Dirt and sludge separator for heating
and cooling water systems or closed
liquid-filled plant systems.

Suitable for the media water and
water/glycol mixtures up to a mixing
ratio of 50/50%.

Integrated high-energy permanent
magnet for separating and fixing of
ferromagnetic parts from the
separation process. Magnet comprises an
isostatically pressed neodymium-iron-
boron rod inserted in a screw-in
immersion sleeve. Particles can be
permanently and deliberately removed
from the fluid flow by screwing the
magnet sleeve out of the separator
housing and then cleaning it.

The cleaning and emptying of the dirt
collection chamber is possible via
a dedicated desludging ball valve
without any necessity to interrupt
operation.

Merkmale

Type: D 22 VM
Housing material: Messing
Installation model: vertikal
Connection type: Klemmring
System connection: 22 mm
Drain connection: G 3/4
max. operating pressure: 10 bar
max. operating temperature: 110 °C
max. flow: 1,25 m³/h
kvs: 10,7 m³/h
Length: 104 mm
Height: 165 mm
Diameter: 65 mm
Weight: 1,55 kg



11.03.2020 19:19

Reflex Winkelmann GmbH

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • www.reflex.de
Geschäftsführer: Norbert Hülsmann, Volker Mauel
USt.-Ident.-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen