## Reflex Exdirt D 1 V, threaded dirt separator, 110 °C, 10 bar Article-No.:9252520



Reflex Exdirt, dirt and sludge separator for heating and cooling systems respectively for sealed system circuits.

Suitable for use with water and water/glycol mixture to a maximum of 50% concentration.

Fitting for the removal of dirt particles up to a size of 5,0 µm out of the liquid flow by way of a specifically designated insert.

The collection area can be easily emptied at regular intervals using a drain ball valve while the system remains in operation. The flanged collection chamber can be removed for inspection.

## Merkmale

Type: D 1 V

Housing material: Messing
Installation model: vertikal
Connection type: Gewinde
System connection: IG 1
Drain connection: G 3/4
max. operating pressure: 10 bar
max. operating temperature: 110 °C

max. flow: 2,0 m³/h kvs: 17,2 m³/h Length: 84 mm Height: 172 mm Diametre: 65 mm Weight: 1,8 kg



11.03.2020 19:18

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • www.reflex.de Geschäftsführer: Norbert Hülsmann, Volker Mauel

USt.-Ident-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen