

Reflex Exdirt D 125, Dirt separator
Flanged connection, 110°C, 10 bar
Article-No.:8252340



Reflex Exdirt,
dirt and sludge separator for heating
and cooling systems respectively for
sealed system circuits.

Suitable for use with water and
water/glycol mixture to a maximum of 50%
concentration.

Fitting for the removal of dirt par-
ticles up to a size of 5,0 µm out of
the liquid flow by way of a specifi-
cally designated insert.

The collection area can be easily
emptied at regular intervals using a
drain ball valve while the system re-
mains in operation. The flanged collec-
tion chamber can be removed for inspec-
tion.

Merkmale

Type: D 125
Housing material: Stahl lackiert
Installation model: horizontal
Connection type: Flansch
System connection: DN125/PN16
Drain connection: IG 1
max. operating pressure: 10 bar
max. operating temperature: 110 °C
max. flow: 72 m³/h
kvs: 351,3 m³/h
Length: 635 mm
Height: 811 mm
Diameter: 354 mm
Weight: 35 kg



11.03.2020 19:07

Reflex Winkelmann GmbH

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • www.reflex.de
Geschäftsführer: Norbert Hülsmann, Volker Mauel
USt.-Ident-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen